

FEEDING DEVICE FOR A TABLE SAW

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a feeding device, and more particularly to feeding device for a table saw. The feeding device of the present invention can be used to a long distance cutting.

2. Description of Related Art

A conventional feeding device for a table saw comprises a moving seat slidably mounted on one side of a worktable of the table saw. A graduation plate is partially rotatably mounted to the moving seat and a pushing rod laterally extends from the graduation plate for abutting against a datum of a workpiece. A threaded rod upwards extends from the moving seat and penetrates through the graduation plate. A nut is screwed onto the threaded rod to hold the graduation plate in place after adjusting an operating angle.

However, the adjusting range of the graduation plate on the conventional feeding device for a table saw is smaller than 180 degrees. Consequently, the conventional feeding device for a table saw is useless when the workpiece is greater than the distance between the pushing rod and the saw blade. Furthermore, the quality of cutting cannot be effectively controlled when the nut is loosened from the threaded rod due to a vibration of the table saw during operating. Consequently, the conventional feeding device for a table saw in accordance with the prior art needs to be advantageously altered.

The present invention has arisen to mitigate and/or obviate the disadvantages of the conventional feeding device for a table saw.

SUMMARY OF THE INVENTION

The main objective of the present invention is to provide an improved feeding device for a table saw. The feeding device of the present invention can be used to a long distance cutting.

To achieve the objective, the feeding device for a table saw in accordance with the present invention comprises a sliding board slidably mounted on one side of a worktable of the table saw and having a moving direction corresponding to a saw blade. The sliding board includes two grooves defined in two opposite sides thereof and respectively parallel to the moving direction of the sliding board. A moving seat is selective slidably mounted on one side of the sliding board. A pushing rod is laterally slidably mounted to the moving seat and has a first side forming a pushing face for abutting against a datum of a workpiece. A first locking device and a second locking device respectively extend through the pushing rod and the moving seat to selectively hold the pushing rod and the moving seat in place for confirming a cutting angle of the workpiece.

Further benefits and advantages of the present invention will become apparent after a careful reading of the detailed description with appropriate reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective schematic view of a feeding device for a table saw in accordance with the present invention;

Fig. 2 is a partially perspective view of the feeding device in Fig. 1;

Fig. 3 is a partially exploded perspective view of the feeding device in

Fig. 1;

Fig. 4 is a front plan view in partial cross-section of the feeding device in Fig. 1;

Fig. 5 is a top plan view of the feeding device in Fig. 1;

Fig. 6 is an operational top plan view of the feeding device in Fig. 1 for a short distance cutting;

Fig. 7 is an operational top plan view of the feeding device in Fig. 6 when the feeding is forwards moved;

Fig. 8 is an operational top plan view of the feeding device in Fig. 1 for a long distance cutting; and

Fig. 9 is an operational top plan view of the feeding device in Fig. 8 when the feeding is forwards moved.

DETAILED DESCRIPTION OF THE INVENTION

Referring to the drawings and initially to Figs. 1-3, a feeding device for a table saw in accordance with the present invention comprises sliding board (10) adapted to be slidably mounted on one side of a worktable of the table saw and having a moving direction adapted to correspond to a saw blade of the table saw. A moving seat (20) is selectively slidably mounted on one side of the sliding board (10). A pushing rod (30) is laterally slidably mounted to the moving seat (20). A first locking device (40) and a second locking device (50) respectively extend through the pushing rod (30) and the moving seat (20) for confirming a cutting angle of a workpiece. A graduation plate (60) is securely mounted to a bottom of the moving seat (20).

The sliding board (10) includes two grooves (11) defined in two

1 opposite sides thereof. The two grooves (11) are respective parallel to the
2 moving direction of the sliding board (10).

3 The moving seat (20) includes a rail (21) laterally extending therefrom
4 and having a T-shaped cross-section. A bore (22) is defined in and extending
5 through the moving seat (20). A steel ball (23) is movably received in the bore
6 (22) and partially extending through a bottom of the moving seat (20). A spring
7 (24) is longitudinally compressively received in the bore (22) and a bolt (25) is
8 partially screwed into the bore (22) to hold the spring (24) and the steel ball (23)
9 in place. An indicator (26) is detachably mounted to a first end of the moving
10 seat (20) for indicating the rotating angle when the moving seat (20) is rotatably
11 moved relative to the graduation plate (60).

12 The pushing rod (30) includes a first side and a second side opposite to
13 the first side of the pushing rod (30). The first side of the pushing rod (30) forms
14 a pushing face (31) adapted to abut against the workpiece and the second side of
15 the pushing rod (30) has a sliding groove (32) laterally defined in the pushing
16 rod (30). The sliding groove (32) includes a cross-section having a shape
17 corresponding to that of the rail (21). The rail (21) of the moving seat (20) is
18 slidably received in the sliding groove (32) in the pushing rod (30) such that the
19 pushing rod (30) can be moved relative to the moving seat (20) when the first
20 locking device (40) is detached from the pushing rod (30) and the second
21 locking device (50) is loosened.

22 A distance between the first locking device (40) and the saw blade of the
23 table saw is shorter than that between the second locking device (50) and the
24 saw blade of the table saw. The first locking device (40) includes a threaded rod

(41) rotatably extending through the pushing rod (30). The threaded rod (41) has a handle (411) extending therefrom for easily operating the threaded rod (41). The handle (411) has a diameter greater than that of the threaded rod (41) and abuts on a top surface of the pushing rod (30). A sliding block (42) is slidably received in a corresponding one of the two grooves (11) in the sliding board (10) and has a threaded hole (421) defined in the sliding block (42). The threaded hole (421) extending through the sliding block (42) and the threaded rod (41) screwed into the threaded hole (421) to hold the sliding block (42) in place. The second locking device (50) is the same as the first locking device (40). The second locking device (50) has a threaded rod (51) extending through the moving seat (20) and having a handle (511) extending from the threaded rod (51). A sliding block (52) is slidably received in a corresponding one of the two grooves (11) in the sliding board (10). The sliding block (52) of the second locking device (50) has a threaded hole (521) defined therein and extending through the sliding block (52). The threaded rod (51) of the second locking device (50) is screwed into threaded hole (521) in the sliding block (52) of the second locking device (50) to hold the sliding block (52) of the second locking device (50) in place.

The graduation plate (60) is attached to the sliding block (52) of the second locking device (50). The graduation plate (60) has a multiple dimples (61) defined therein for partially receiving the steel ball (23). Each dimple (61) is situated on a certain angle for quickly orientating the moving seat (20) and the pushing rod (30) in the certain angle. The graduation plate (60) has a series of scales (62) formed on an arc edge thereof and corresponding to the indicator

1 (26) of the moving seat (20) for indicating the operating angle of the moving
2 seat (20) and the pushing rod (30).

3 With reference to Fig. 4 and 5, the moving seat (20) and the pushing rod
4 (30) can freely adjusting the operating angle when the first locking device (40)
5 and the second locking device (50) are loosened. The user can clearly read the
6 operating angle via the indicator (26) and the series of scales (62) on the
7 graduation plate (60) when the moving seat (20) and the pushing rod (30) is
8 adjusted.

9 With reference to Figs. 6 and 7, the pushing face (31) forwards abuts
10 against a datum of the workpiece for a short distance cutting. With reference to
11 Figs. 8 and 9, the indicator (26) is detached from the moving seat (20) and
12 attached to a second end of the moving seat (20). The threaded rod (41) is
13 detached from the sliding block (42) and the pushing rod (30) and the threaded
14 rod (51) of the second locking device (50) is loosened. The threaded rod (41) of
15 the first locking device (40) is screwed into threaded hole (421) in the sliding
16 block (42) of the first locking device again to hold the sliding block (42) of the
17 first locking device (40) in place after the moving seat (20) turning about 180
18 degrees and the threaded rod (51) of the second locking device (50) being
19 tightened again. Then, the pushing face (31) of the pushing rod (30) backward
20 abuts a datum of workpiece that needs a long distance cutting. For the long
21 distance cutting, the user forwards pushes the workpiece with the feeding
22 device of the present invention to finish the long distance cutting of the
23 workpiece.

24 As described above, the feeding device for a table saw in accordance

1 with the present invention has the following advantages.

2 1. The work range of the feeding device of the present invention is
3 greater than that of the conventional feeding device for a table saw. The feeding
4 device can be provided for a great workpiece that needs a long distance cutting
5 after turning the moving seat (20) about 180 degrees.

6 2. The first locking device (40) and the second locking device (50)
7 provide a stable support to the pushing rod (30) during cutting.

8 3. The first locking device (40) and the second locking device (50)
9 hardly automatically loosen at the same time such that the relation between the
10 pushing rod (30) and the moving seat (20) is stable.

11 4. The operating angle of the feeding device is easily adjusted because
12 the user only needs to loosen the first locking device (40) and the second
13 locking device (50) before adjusting the operating angle of the feeding device in
14 accordance with the present invention.

15 Although the invention has been explained in relation to its preferred
16 embodiment, it is to be understood that many other possible modifications and
17 variations can be made without departing from the spirit and scope of the
18 invention as hereinafter claimed.